


P1265 PROJECTOR

DLP Technology – Ultra portable

Acer P1265 combines extra portability and excellent colour reproduction to form the ultimate presentation tool. The Acer P1265 is well suited for the most demanding Multimedia presentation applications

Why P1265 Projector?

- Resolution XGA (1024 X 768), SXGA (1400 x 1050)
- Contrast Ratio 2000:1
- Brightness 2,400 ANSI Lumens
- Projection Distance 3.3' (1.0m) ~ 39.0' (11.9m)



Technical Specifications

Model Name	P1265
Resolution	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2000:1
Displayable Colours	16.7 Million Colors
Brightness	2,400 ANSI Lumens (Standard), 1,920 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal Scan Rate	31.5 – 100 kHz
Vertical Scan Rate	56 – 85Hz
Lamp Type / Life	180 W user replaceable P-VIP lamp / 3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 2 watts Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2x
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	230 Watts (Operation), 10 Watts (Standby)
Operating Temperature	5 – 35 Degrees
Noise Level	28 dBA (Standard mode), 24 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1 , DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 1
Output Interface	Analog RGB (D-sub) x 1
Control Interface	USB (Type B) x 1 RS232 (Mini DIN) x 1
Weight and Dimensions	3.0kg 299 x 229 x 93 mm (11.8" x 9.0" x 3.7")
Compliance	C-Tick (AS/NZS 60950)
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.

¹ Specifications vary depending on model.